

MODEL	INSIDE DIMENSIONS (inches)			OUTSIDE DIMENSIONS (plus overall depth)			A (access 90°)	B (152°)	C (180°)	D (90°)	CAPACITY (cu. ft.)	WEIGHT (lbs.)
	Height	Width	Depth	Height	Width	Depth (OD)						
PRO6 1212	12	12	11	17 ¹ / ₈	17 ¹ / ₈	19 (20 ¹ / ₂)	7 ¹ / ₂	27 ¹ / ₄	30 ³ / ₄	34 ¹ / ₄	0.92	355
PRO6 1414	14	14	12	19 ¹ / ₈	19 ¹ / ₈	20 (21 ¹ / ₂)	9 ¹ / ₂	31 ¹ / ₄	34 ³ / ₄	37 ¹ / ₄	1.36	450
PRO6 1616	16	16	16	21 ¹ / ₈	21 ¹ / ₈	24 (25 ¹ / ₂)	11 ¹ / ₂	35 ¹ / ₄	38 ³ / ₄	43 ¹ / ₄	2.37	620
PRO6 1814	18	14	12	23 ¹ / ₈	19 ¹ / ₈	20 (21 ¹ / ₂)	9 ¹ / ₂	31 ¹ / ₄	34 ³ / ₄	37 ¹ / ₄	1.75	510
PRO6 2414	24	14	12	29 ¹ / ₈	19 ¹ / ₈	20 (21 ¹ / ₂)	9 ¹ / ₂	31 ¹ / ₄	34 ³ / ₄	37 ¹ / ₄	2.33	610
PRO6 2416	24	16	16	29 ¹ / ₈	21 ¹ / ₈	24 (25 ¹ / ₂)	11 ¹ / ₂	35 ¹ / ₄	38 ³ / ₄	43 ¹ / ₄	3.55	750
PRO6 3016-12	30	16	12	35 ¹ / ₈	21 ¹ / ₈	20 (21 ¹ / ₂)	11 ¹ / ₂	35 ¹ / ₄	38 ³ / ₄	39 ¹ / ₄	3.33	675
PRO6 3016-16	30	16	16	35 ¹ / ₈	21 ¹ / ₈	24 (25 ¹ / ₂)	11 ¹ / ₂	35 ¹ / ₄	38 ³ / ₄	43 ¹ / ₄	4.44	930
PRO6 3020	30	20	16	35 ¹ / ₈	25 ¹ / ₈	24 (25 ¹ / ₂)	15 ¹ / ₂	43 ¹ / ₂	46 ³ / ₄	47 ¹ / ₄	5.56	990
PRO6 3620	36	20	16	41 ¹ / ₈	25 ¹ / ₈	24 (25 ¹ / ₂)	15 ¹ / ₂	43 ¹ / ₂	46 ³ / ₄	47 ¹ / ₄	6.67	1,100
PRO6 4016	40	16	12	45 ¹ / ₈	21 ¹ / ₈	20 (21 ¹ / ₂)	11 ¹ / ₂	35 ¹ / ₄	38 ³ / ₄	39 ¹ / ₄	4.44	960
PRO6 4820	48	20	16	53 ¹ / ₈	25 ¹ / ₈	24 (25 ¹ / ₂)	15 ¹ / ₂	43 ¹ / ₂	46 ³ / ₄	47 ¹ / ₄	8.89	1,390
PRO6 6020	60	20	16	65 ¹ / ₈	25 ¹ / ₈	24 (25 ¹ / ₂)	15 ¹ / ₂	43 ¹ / ₂	46 ³ / ₄	47 ¹ / ₄	11.11	1,665
PRO6 6026	60	26	16	65 ¹ / ₈	31 ¹ / ₈	24 (25 ¹ / ₂)	21 ¹ / ₂	54 ¹ / ₄	58 ³ / ₄	53 ¹ / ₄	14.44	1,925

Professional Series (2010) / Explanations of Codes

A: straight-in access width when door is open 90°

B: overall width of safe+door when open 152° (required for installation of a full width internal cabinet)

C: overall width of safe+door when open 180°

D: overall depth of safe+door when open 90°

(OD): overall depth of safe including hinge and handle projection