

GIANT SECURITY

Technical Data Sheet 

SAFE RANGE S.A.B.S. CATEGORY III

The main feature of the Giant Category III range of Safes is the CERASTRA Armour, which is in every way technically superior to the Standard T.D.R. protection currently available.

The major markets for this range embrace the financial institutions, jewellery and bullion industry as well as large Government and commercial outlets.

SPECIFICATION

Armour Type: CERASTRA Armour (Patent pending) 100 mm thickness.

Resistance to attack: Subject to C.S.I.R. report No. ME1615/1 (Test thickness 100 mm) 8th May 1979 available on request.

Oxy-acetylene	4 - 5 hours
Oxy-arc	Not possible
Drill	7 - 8 hours
Angle Grinder	Not possible

Dimensions:		TYPE	3225	3429	3929	4429	5629	6529
OUTSIDE	Height mm	825	875	1000	1130	1445	1690	
	Width mm	650	750	750	750	750	750	
	Depth mm	735	810	810	810	810	810	
INSIDE	Height mm	570	620	750	875	1180	1410	
	Width mm	395	495	495	495	495	495	
	Depth mm	395	470	470	470	470	470	
MASS kg		890	1100	1300	1540	1660	2200	

Locking Mechanism: 1 Four Wheel combination lock is fitted capable of 10^8 combinations. Giant Security has developed an electronic combination lock as an optional extra.

In addition two high precision 8 lever key locks are fitted. All locks are protected by unique relocking devices which automatically deadlock the boltwork if the lock is attacked by explosives.

Boltwork: The door is secured and controlled by hardchrome plated bolts 45 mm diameter.

Internal Fittings:

Type 3225, 3429	1 adjustable shelf & 2 drawers
3929	2 adjustable shelves & 2 drawers
4429, 5629	3 adjustable shelves & 2 drawers
6529	4 adjustable shelves & 2 drawers

